

Original Article

Revolutionizing Technology: Exploring the Applications of Quantum Physics in Computing

Gokul G¹, Ishwarya²^{1,2} UG Scholar Bharathidasan University, Tiruchirappalli, Tamil Nadu.

Received Date: 25 August 2025

Revised Date: 22 September 2025

Accepted Date: 15 October 2025

Abstract: Quantum mechanics, a subject that was once the province of only basic physics but which is now causing a major upheaval in computing. In this paper will be discussed how can quantum-physical principles, such as interference, entanglement and superposition are useful in order to try to build a new model for processing (quantum computing). We begin with the physics of quantum information and describe how qubits, not classical bits, are used to store and process information. After that, we point out important algorithmic advances to factoring integers and search in high dimensions, and we stress how quantum simulation of many-body systems can achieve an advantage exceeding the best classical methods. We next discuss the hardware roadmap and trade-offs between coherence time, connectivity, gate fidelity and scalability. These consist of superconducting circuits, trapped-ion platforms, photonics devices, spin-based qubits and emerging topological procedures. Applications are then reviewed such as secure quantum-key distribution and this cryptography becoming susceptible to cryptanalytic attack for classical encryption, materials design and plant simulation in chemistry and condensed matter physics, logistics modelling etc., in business and finance, new domain such as quantum machine learning or physical system simulation. The severe difficulties are criticized in a critical paragraph. These open problems include the algorithmic question of where does true quantum advantage lie, the need for software-hardware co-design and control imperatives, the engineering challenge of scaling to many qubit fault-tolerant systems, resorting to huge overheads with fault-tolerance approaches based on quantum error correction, and most importantly prevailing issues concerning decoherence and error accumulation. We also reflect on broader societal implications (social, economic and moral), including security shifts, work force readiness, disparities of access, dual use considerations as well as the worldwide global competitive context. We close with a proposed roadmap consisting of multiple tiers: near-term focus on application-specific demonstrations and noisy intermediate-scale quantum (NISQ) systems; medium-term pursuit of building small fault-tolerant modules and hybrid quantum-classical computing; and long-term vision of constructing large-scale fault-tolerant quantum processors that power disruptive applications.

Keywords: Quantum Computing, Qubit, Superposition, Entanglement \ Quantum Algorithms, Quantum Simulation, Fault-Tolerance, Quantum Error Correction, \ Quantum Advantage, Quantum Hardware. The Paper Calls For An Orchestrated Strategic Funding In Hardware, Algorithms, Software And Governance To Ensure Quantum-Computing Is Delivered Responsibly And With Benefit.

I. INTRODUCTION

The rapid advance of classical computing, from vacuum tubes to transistors to present multi-core microprocessors, has transformed civilization by enabling high performance scientific simulation, digital communication, artificial intelligence and countless other applications that we now take for granted as part of our modern way of life. But, while technology continues to become more advanced, there is a fundamental limit. The asymptotic wall of the classical paradigm. Some classes of problems meet an asymptotic wall in the classic sense, such as those for complex linear algebra, combinatorial explosion, and high-dimensional quantum systems. A second distinct model of computation is presented by quantum computing, which lies at the interface between computer science and quantum physics. Quantum machines are also supposed to be able to investigate solution spaces classical devices cannot possibly reach, due to the proper use of peculiar quantum mechanics phenomena like quantum interference (the ability of canceling wrong answers by way of phase coherence and amplifying right ones), entanglement (non-classical correlations between qubits that allow joint behavior far beyond classical independence) and superposition (quality for a quantum bit or “qubit” of being in more than one state at once).

We need to recognize the shift in what information means from a classical bit (0 or 1) to a quantum one (a superposition $\alpha|0\rangle + \beta|1\rangle$ where $|\alpha|^2 + |\beta|^2 = 1$). It is important to understand what we can expect from quantum computing. Although aptly named, the representation is capable of modeling a quantum circuit processing operations in a Hilbert space with an exponential depth when its circuit size (read: number of qubits) grows. What’s more, entanglement binds qubits in a way that keeps them all effectively part of the



same whole – one state that cannot be divided into separate pieces, and it is this particular property which unlocks behaviours without parallel in the classical world. The term "quantum advantage" refers to situations where a quantum computer is able to perform some calculation with asymptotic or practical scaling advantage compared with its most widely-known classical analogue.

In the early 1980s and '90s, intrepid souls like David Deutsch and Richard Feynman made a series of imaginative proposals that laid down the theory behind quantum computing. Deutsch formulated a universal quantum computer model and meanwhile Feynman proposed that any change in physics should make computation (e.g. simulation) easier rather than harder for reasons of practicality. Since that time, algorithms have achieved clear theoretical speed increases on specific tasks, given by e.g. Lov Grover's search algorithm and Peter Shor's factoring method. For example, Grover's algorithm provides us with a quadratic speed-up for unsorted search problems and Shor's This paper is organized as follows.

Hardware, with its theoretical development, has advanced impressively. A diverse range of physical qubit platforms is being developed, such as Si-based spin qubits, photonic circuits, trapped ion systems, superconducting qubits and experimental topological qubits. The pros and cons of each of these platforms are as follows: photonic systems promise room-temperature operation and networking, but have challenges with deterministic gate operations; spin systems coupled to standard semiconductor fab pathways suggest eventual scalability; topological schemes are mostly experimental but aim at encoding information in intrinsically protected quantum states; superconducting systems deliver fast gates, but rely on ultra-low temperatures and suffer coherence limitations; trapped ions offer high fidelity and long coherence (at the expense of slower gate rates).

Quantum computing applications rely on the intersection of algorithms, hardware, and software. These applications can be generally grouped into several categories. In security and cryptography, quantum computers allow both new protocols such as QKD offering information-theoretic security, and break commonly-used ones (through algorithms such as Shor's). Quantum simulation promises to be enormously more powerful than classical techniques for simulating molecular electronic structure, reaction dynamics and material physics in chemistry and materials science. Quantum-enhanced algorithms (like different steps in the quantum approximate optimization algorithm, or quantum annealing) are applied to logistics and optimisation, where complex combinatorial problems can be solved in a variety of industries. Quantum approaches offer both novel subroutines of linear algebra or embedding strategies for machine learning and data analysis but it is still uncertain whether there is a clear quantum advantage in real ML tasks. In addition, concepts in basic physics such as many-body dynamics and emergent phenomena can be studied using quantum devices. But there is a catch when it comes to large-scale, practical quantum computing. Quantum states are prone to noise in their environment and decoherence due to their intrinsic fragility; measurement interrupts quantum evolution, while the superposition collapses; and at higher levels of circuit depth error aggregations and gate imperfections compound rapidly. While QEC has a substantial overhead in physical qubits per logical qubit, it offers the hope of mitigating these problems. Thus improvements in qubit fidelity, connectivity, architecture and control electronics, as well as cryogenics and interconnections are required to scale to fault-tolerant quantum computers. In addition the software stack—compilers, optimisers and runtime systems—needs to mature in order to facilitate hybrid quantum-classical workflows and efficiently map algorithms onto hardware constraints. Discovering real-world problems for which quantum advantage is provable and practically affordable still remains a major challenge at a complexity point of view.




Figure 1: Schematic of Electron-Phonon Coupling in Ultrafast Material Dynamics

Besides technical aspects, quantum computing entails serious ethical and social implications. The advance toward quantum-breakers for computational encryption could destabilize existing communication and security networks; geopolitical power structures might change as countries compete over quantum technology; asymmetries in the global

system of power relations may be exacerbated by access to or concentration of quantum-capable infrastructure. Commercial dual-use considerations also arise because powerful quantum systems could be used for both harmful disruption and beneficial scientific results. Hence, open standards, education initiatives and responsible research and governance frameworks are crucial to ensure the quantum computing revolution is harnessed for society's benefit as a whole, rather than exacerbating inequality.

The ambition of this work is to survey the current status and prospects of quantum computing in this context, ranging from hardware systems and domain-specific applications to algorithmic advances and physical principles, as well as addressing possible emerging technical obstacles or strategic opportunities. It argues that transformational impact requires deliberate attention to workforce development and governance, as well as coordinated movement on multiple levels. Additional examination of fundamental physical principles, a description of major algorithms and associated complexity results, hardware landscape mapping, application domains overview, crosscutting issues analysis and short-, medium- and long-term future roadmaps are covered in the subsequent parts. Our aim is to give researchers, engineers, policy makers and business people both a global perspective on the promise of quantum physics and also a sense of community about the steps that need to get done to—in so many words—turn potential into reality.

II. BACKGROUND: QUANTUM MECHANICS MEETS INFORMATION

Quantum computing is a complete redesign of computation, based on the principles of quantum mechanics. Quantum computers take advantage of the strange, counterintuitive properties of quantum physics to process information in ways that are fundamentally different from a classical computer operating according to deterministic rules for the manipulation of bits. The main mathematical and physical properties of the quantum computation are described, focusing on qubits, superposition, entanglement, interference and measurement. Together, these events constitute the basis for quantum information theory and the concepts behind quantum hardware architectures and algorithms.

A. One Qubit or the Unit of Quantum Information

The quantum bit, or qubit, is the elementary unit of quantum information and the fundamental building block for quantum computing. One classic bit can exist in only 2 states at any time: 0 or 1. On the other hand, states $|0\rangle|0\rangle|0\rangle$ and $|1\rangle|1\rangle|1\rangle$ describe a two level quantum system in which there is one qubit present obeying quantum mechanical rules. Unlike the value 0 or 1, if one atom is projected into a superposition of two states, the qubit in that case will also be in a superposition of two base states and can be described by performed this as:

$$|\psi\rangle = \alpha|0\rangle + \beta|1\rangle \quad |\psi\rangle = \alpha|0\rangle + \beta|1\rangle$$

$|\alpha|^2 + |\beta|^2 = 1$, with α and β complex probability amplitudes satisfying the normalisation condition. The squares of these amplitudes give the probabilities of observing the qubit in state $|0\rangle|0\rangle|0\rangle$ and $|1\rangle|1\rangle|1\rangle$, respectively, upon measurement.

Depending on the technology platform, there are several ways in which a qubit can be implemented prioritarilly. An electron's spin direction, a photon's polarisation, an atom's energy levels or the path of a superconducting loop's circulating current are some. Two fundamental requisites of any implementation are that it should allow to control the processing of information with high precision, using controlled transformations (quantum gates), and allow for maintaining a coherent superposition over some range of possible interactions.

B. Superposition: Expansion of the Computational Space

Suppose that, at the root of quantum computing power lays superposition, one of the great ideas in quantum physics. A string of n bits in a classical computer can encode just one of the 2^n possible states, because each bit can represent only one state at a time. By contrast, a system of n quantum bits, or qubits, can simultaneously be in a superposition over all 2^n possible states. It is this specific attribute, or what's often referred to as "quantum parallelism," that allows quantum computers to perform massive combinations of data in parallel.

Let's consider here a 2-qubit system. $|00\rangle, |01\rangle, |10\rangle, |11\rangle$ are the basis states. A state of superposition might look like this:

These 1-bit operations can be illustrated easily, by using the state (A.1) in a computational basis, for which one finds $|\psi\rangle = \frac{1}{\sqrt{2}}(|00\rangle + |01\rangle + |10\rangle + |11\rangle)$.

That here means that you have a single quantum system which contains every combination of bit values at the same time. Taking advantage of this phenomenon, quantum algorithms process all elements of the superposition simultaneously and some calculations are able to run exponentially faster than their classical counterparts. Note that measurement collapses the state to a single classical one, so superposition doesn't give you multiple possibilities directly. Rather, techniques should be devised to improve the probability of correct answer by employing quantum interference.

C. Entanglement: Correlation Without Local Cause

Entanglement, the most powerful and mysterious characteristic of quantum mechanics. When two or more qubits become entangled, they no longer possess states independent of one another; the entire system must be described by a single wave function that cannot be written as the product of the wave functions of its constituent parts. In other words, no matter how far apart two qubits may be, the state of one immediately influences that of the other a spooky action at a distance, as Albert Einstein famously dismissed it.

The Bell state as an example of entangled state:

E.g., $|\Phi^+\rangle = \frac{1}{\sqrt{2}}(|00\rangle + |11\rangle)$

In this situation, neither qubit is at an absolute 0 or 1. The specific outcome is uncertain until measured, and the pair occupies a superposition of being both 0 and 1. Entanglement, an important state of matter, makes quantum teleportation, superdense coding and secure quantum key distribution possible.

Computationally, entanglement enables quantum gates to produce correlations among qubit values, which exponentially increases the system's representational capability. An entangled qubit register, for example, can encode complex problem topologies and facilitate the realization of algorithms that rely on collective states to simulate multi-particle quantum systems or identify global optima. As a result, the quantum advantage demonstrated in various algorithms and simulations is based on entanglement.

D. Non-Inhibitive and Inhibitive Computational Interference

Interference is what allows quantum systems to home in on the right answers despite superposition, which spreads them across multiple states. This wave-like nature of probability amplitudes leads to quantum interference – where different computational pathways can interfere destructively (eliminating bad outputs) or constructively (reinforcing good ones). A simple analogy to imagine is the interference pattern of light waves: Waves interfere additively when they are in phase with each other and we see dazzling fringes, while they cancel each other out when out of phase and we register darkness. Similarly, quantum algorithms are designed in such a way that the amplitudes of right answers interfere constructively and those for wrong ones do so destructively.

This is best illustrated by the Grover search algorithm. Through iterated interference, it amplifies the probability amplitude of the correct answer and reduces the query complexity of a solution from $O(N)O(N)O(N)$ queries in classical search to approximately $O(\sqrt{N})$ searches in quantum search. As a result, phase coherence and minimizing environmental noise are critical for the algorithm's performance, which is largely predicated on the ability to operate phase and amplitude coherently.

E. The Measurement: Linking Classical and Quantum Worlds

Measurement is the border between quantum mechanics and classical physics. As is implied by the Schrödinger equation, a quantum system evolves deterministically and unitarily before being probed or measured. On measurement the system's wavefunction is projected randomly into one of the potential eigenstates and we obtain an outcome probabilistically from the squared magnitudes of the amplitudes. For instance, if one measures a qubit in the state $|\psi\rangle = \alpha|0\rangle + \beta|1\rangle$ with probability $|\alpha|^2$ and $|\beta|^2$. The superposition simply doesn't exist for the system after measurement, and information about phase relations between amplitudes is lost forever. This has as its corollary both a challenge and an opportunity within quantum computing. While the fact that measuring a superposition precludes direct access to the complete information it carries is regrettable, on the other hand statistics post processing and probability algorithms can be applied on quantum operations to obtain useful results.

Thus, in quantum algorithms attempts are made to improve the probability that when an observation is made it will lead to the intended/true outcome. By careful interplay of gate sequences and interference patterns, the final quantum state has constructive probability amplitude concentrated at the correct solution. Moreover, measurement in different bases is indispensable in state verification, tomography and quantum error correction.

F. Quantum Computation Model

The characteristic features of the phenomena described above correspond to the quantum computational model: measurement, entanglement, interference and superposition. Quantum gates – reversible, linear, and unitary operators acting on the qubits – are performed for quantum computing. Including the Pauli-X, Hadamard (H) and Controlled-NOT (CNOT) gates – these are among the gates that govern qubit amplitudes and entanglement. A string of these gates constitutes a quantum circuit, which is akin to a logical circuit in classical computing. Global probability over all possible states is preserved via computation, as quantum evolution is unitary. Only measurement turns usual quantum information

into classical results by bringing in non linearity and irreversibility. For practical quantum computation, efficient quantum circuits that exploit superposition and entanglement while avoiding decoherence need to be developed.

Finally, it is the interplay of several distinct quantum effects that makes quantum computing so extraordinarily powerful. Measurement connects quantum dynamics with classical reality, interference directs computation to the right answer, entanglement allows non-local correlations, superposition extends the computational landscape and it is all rooted in the qubit. The combination of these ideas yields a powerful new framework for computation that escapes classical limitation and enables radical advancements in technology, business, and science.

III. CORE QUANTUM ALGORITHMS AND COMPLEXITY

What makes quantum computing different from classical, is its quantum algorithms. The algorithms are that which transforms this quantum potential into computational advantage, despite the hardware providing us with practical realisation of quantum mechanics. Quantum algorithms are significantly faster than classical algorithms in searching large solution spaces via superposition, entanglement and interference. Our understanding of computational complexity and problem solvability has evolved a great deal in the past thirty years due to several important algorithms that exhibit exponential or polynomial speedups, relatively when compared to the most famous classical ones.

Algorithm by Peter Shor, 1994 It is one of the most inventive contributions to the field. It computes discrete logarithms in polynomial time with respect to the number of bits of the input integer, and solves the problem of factorising integers. The importance of such an achievement cannot be overstated, as it immediately brings into question the security foundations of modern public-key cryptosystems, such as RSA, Diffie-Hellman and elliptic-curve cryptography that rely on the hardness of these mathematical problems. In order to efficiently detect the period of modular arithmetic functions, a task which is classically exponentially slow, Shor's method utilizes quantum Fourier transforms. The algorithm discovers the period of a function which reveals prime factors of any large integer, using interference and coherent superpositions. This is an exponential improvement over well known classical algorithms such as the general number field sieve, which has sub-exponential (but super-polynomial) time complexity. Due to the enormous cybersecurity consequences, post-quantum cryptographic algorithms that are resistant against attacks using quantum computers have to be deployed as soon as possible. Although the algorithm makes use of quantum computers that are fault-tolerant and require tens or millions of logical qubits to work at scale, its conceptual proof is often referred to as one of the milestones in the theory of quantum computing.

The search algorithm of Grover, whose first version was published by Lov AdvertisementAdvertisementgrover in 1996, is a second core quantum algorithm. Grover's algorithm attacks one of two kinds of search problem, namely a general search or a search on an unstructured database, with a quadratic speed-up. Classically, manually finding a specific element from an unordered list of NNN elements takes $O(N)O(N)O(N)$ operations because to find that item you might have to look at each item in turn. Grover's algorithm, in contrast, performs this in $O(N)O(\sqrt{N})O(N)$ iterations. By using quantum interference to repeatedly amplify the amplitude of the correct solution [1], the algorithm must ensure that while using this kind of replication process, the probability with which we can measure the correct solution increases at each iteration. A quadratic speed-up may appear less impressive than Shor's algorithm's exponential one, but Grover's method is a fundamental building block of quantum algorithms due to its applicability to many problems including combinatorial optimisation, database search and reversing cryptographic hash functions. It also serves as a template for amplitude amplification techniques, the foundation of many subsequent hybrid methods and quantum algorithms.

Apart from factorization and search, quantum simulation is one of the most compelling and powerful applications of quantum computation. Because the state space of a quantum system grows exponentially with the number of particles, simulating quantum systems on classical computers is inherently inefficient (an insight already observed by Richard Feynman in the early 1980s). On the flip side, since they can represent and manipulate quantum states natively, quantum computers would be great for simulating complex materials, chemical reactions and structures of molecules. Quantum simulation algorithms are designed to utilize the underlying linear algebraic structure of quantum mechanics for the purpose of solving the Schrödinger equation, describing many-body interactions and computing ground state energies of molecules. This capability is particularly valuable in condensed matter physics, quantum chemistry and materials design, where understanding molecular dynamics or reaction mechanisms may lead to energy storage enhancement, the development of new medications or nanotechnology breakthroughs. Especially in the proximate era of noisy intermediate-scale quantum (NISQ) machines, quantum simulation is often cited as one of the most imminent and important applications of quantum computing.

Fully fault-tolerant algorithms such as Shor's remain out of reach in this NISQ regime: we focus here on hybrid quantum-classical algorithms, which are also known as Variational Quantum Algorithms (VQAs). VQAs provide a connection

between future error-corrected quantum systems and current noisy devices. The concept of VQAs is based on parameterised quantum circuits with the optimisation of its parameters performed classically. The Quantum Approximate Optimization Algorithm (QAOA) and the Variational Quantum Eigensolver (VQE) are two such cases. As quantum hardware computes challenging energy landscapes, and classical optimisers iteratively adapt circuit settings, VQE is particularly suitable for finding ground-state energies of molecular systems. Meanwhile, QAOA uses variational approximations of answers to address combinatorial optimisation problems. They are based on the existence of high-dimensional solution spaces that can be encoded by quantum systems, taking inspiration from them, while in the classical part they mitigate noise and hardware restrictions that affect contemporary processors. By virtue of their performance, VQAs are now the leading candidates to demonstrate near-term quantum advantage in finance, logistics, and chemistry.

Quantum Machine Learning (QML) considering the possibility of which machine learning tasks can be made faster or better by quantum computers, is a rapidly growing direction in quantum algorithm research. In some of these settings QML is better than classical approaches in large-scale linear algebra problems, such as inversion of matrices, eigendecomposition or vector/matrix multiplication exploiting the exponential sizes of quantum spaces. Quantum kernel methods, principal component analysis, and clustering have been realized through quantum feature mappings – methods of embedding classical data into high-dimensional Hilbert spaces. In addition to classical deep learning models, quantum neural networks and parameterised quantum circuits are considered as alternatives. While many QML algorithms remain a theoretical concern or are restricted by the data-loading bottleneck – creating quantum states that can effectively represent large classical data sets – they offer tantalising prospects for generative modelling, pattern recognition and anomaly detection. Moreover, scalable quantum processors of sizes that are accessible in the near term can already implement hybrid QML algorithms that combine the strengths of both quantum feature extraction and classical processing experimentally [6], indicating a possible path to practical applications within the next decade.

Collectively, these basic algorithms—Shor’s and Grover’s as well as the variational models, quantum simulation classes and QML approaches—exemplify the remarkable generality of quantum computation. By demonstrating that some problems previously thought to be unsolvable for classical systems can in fact be better solved using quantum resources, they change the definition of computational complexity. Though problems of scalability, error correction and decoherence remain, the theoretical basis for quantum algorithms is advancing rapidly. Hybrid, probabilistic and topological algorithms are being developed in order to exploit certain hardware architectures and issue structures. The boundary between quantum and classical computation is getting more blurred as research continues, a time may thus come when classical computation will be supplemented rather than replaced with quantum acceleration. After all, quantum algorithms are not just a faster answer to problems we already have in terms of classical computing, they represent an entirely new manner of processing manipulated information—an approach that nature itself has evolved to take.

IV. HARDWARE ARCHITECTURES

One of the most captivating and challenging fields in present technology is the experimental implementation of a quantum computer. This has led to the situation that, contrary to conventional computing where all hardware architectures eventually boil down to binary logic using transistors, a variety of physical platforms are possible for quantum computing, each employing a different aspect of quantum physics to represent and manipulate qubits. The physical principles underlying such schemes, methods of control, coherence properties, and scaling potential are distinct. The primary platforms that are now under development include superconducting qubits, trapped ions, photonic systems, spin-based qubits and topological qubits. Each represents a distinct technological approach to building powerful, useful quantum computers on a large scale.

The superconducting qubit counts amongst the most advanced and commercially available designs. These systems utilise superconducting circuits formed from materials such as niobium or aluminium and cooled to cryogenic temperatures near absolute zero. It is possible to make artificial atoms with discrete energy levels that can be described by the quantum states $|0\rangle$ and $|1\rangle$ at these temperatures because of the circuits' macroscopic quantum behavior. Rapid gate operations, typically performed on a nanosecond time scale, are achieved using microwave pulses which drive transitions between these states and perform quantum information manipulation. Machines with tens to hundreds of qubits are the fruits of big investments in superconducting technology by companies such as IBM, Google and Rigetti. Despite their rapid development, superconducting systems still face several challenges. The two most pressing issues are scalability and decoherence—the loss of quantum information due to interaction with the environment. Upgrades to cryogenic engineering, control electronics and error-correction integration are required to continue increasing the number of qubits while maintaining high-fidelity gates and low crosstalk. However, superconducting qubits are one of the most promising platforms for near-term quantum advantage due to their compatibility with current microfabrication technology and mature manufacturability landscape.

Another promising platform is the trapped-ion quantum computer, where qubits simulate in the internal electronic states of ions confined in electromagnetic traps. These ions may be finely controlled by laser pulses to perform single-qubit

and multi-qubit gate operations. The trapped-ion systems have a remarkable coherence time (usually longer than several seconds) and high gate fidelities ($> 99.9\%$). It has a great advantage with respect to nearest-neighbor coupling in superconducting systems namely all-to-all qubit connectivity which is facilitated by the Theoreticalexplanation The existing theoretical model, originally discussed in [9] and later improved for large system sizes in [21], starts from the Schrodinger equation for the motion of ions inside of the rf trap. However, due to restrictions in ion transport and laser switching those trapped-ion gates tend to be much slower operating at the microsecond or millisecond level. It's still a difficult engineering problem to scale up to larger systems. Yet, companies such as IonQ and Quantinuum and research teams around the world continue to stretch the boundaries of trapped ion quantum processors, demonstrating improved modular architectures and increasing qubit counts.

A third approach, photonic quantum computing, which uses single photons—packets of light—as qubits, is also becoming more prominent. Some characteristics inherent for photons are that they can operate in room temperature, and have long coherence times because their interactions to the environment is weak. In quantum information processing, linear optics elements (such as beam splitters, phase modulators and interferometers) effectively manipulate the quantum information that is encoded in properties such as polarization, phase or path. As photonic systems enable long-range transmission through optical fibres or free-space channels, they are particularly attractive for quantum communication⁴⁶²⁶. They also form the basis for specialised computing models such as boson sampling, in which quantum interference of indistinguishable photons is used to perform actions that are normally impossible. The photonic system is in fact, though, a different story — the essential issue of the photonic processor, and what separates it from an electrical one that you might be familiar with, is being able to make and detect single photons efficiently and accurately. Private companies like Xanadu and PsiQuantum are both leveraging SGD progress in integrated photonics and quantum light sources, which offer promising ways forward for scalable photonic quantum systems that can perform secure communication as well computation. Spin-based qubits, for example those in silicon quantum dots and nitrogenvacancy (NV) centres in diamond provide an alternative intriguing direction. The devices rely on magnetic or microwave fields to manipulate the ‘spin’ of an electron or nucleus — in which a quantum bit is stored. Moreover, as they may be manufactured with existing semiconductor processing methods, silicon spin qubits are particularly attractive for integrating quantum processors and conventional CMOS technology. Yet, despite being at room temperature, diamond’s NV centres have demonstrated an impressively long coherence time which suitable for small-scale quantum networks and sensing applications. Although achieving uniform control over large qubit arrays and suppressing decoherence due to neighboring impurities or lattice vibrations are challenges, spin qubits represent an enticing compromise between the potential for scaling of solid-state devices and long coherence times characteristic of atomic systems.

Topological quantum computing is perhaps the most theoretically interesting, but least mature platform and seeks to encode qubits in topologically non- local states of matter. Information-encoding quasiparticles known as anyons have worldlines that can be “braided,” allowing quantum operations to be performed. Topological qubits are intrinsically protected against some forms of decoherence and operational errors, the encoding being global rather than local in nature. The most celebrated implementation is the formation of Majorana zero modes in two-dimensional materials or superconducting nanowires with non-Abelian statistics. Topological qubits could also give fault-tolerant quantum computing with much lower error correction costs, however experimental demonstration of robust Majorana modes remains a large challenge. All the big research groups are working away testing and controlling these exotic states and such, Microsoft is one of them but there’s lots of them. Each of these topologies has its own trade-offs in gate speed, coherence time, fidelity, connectivity, and scalability. Superconducting systems have fast gates and are industrially scalable, but low coherence times. Although trapped ions boast impressive precision, their ability to efficiently compute is slow and restricted in parallelism. Photonic systems are robust and communicable, but they lack detector efficiency and suffer from photon losses. While the spin qubits demonstrate long coherence times and are compatible with semiconductors, large-scale homogeneity remains unsolved. Topological qubits are, at this point, only theoretical but they may be inherently error-protected.

The challenge with all platforms is how to balance scalability, control and coherence. Improving qubit quality, developing modular and networked systems, and learning quantum error correction methods can map unstable physical qubits into a stable “logical” qubit are the principal objectives of cross-platform research. They're also studying hybrid systems that take the best parts of two or more architectures — such as using spin qubits for quantum memory, or linking superconducting computers by photonic interconnects. Ultimately, there is no one technique that is presently a clear winner for large-scale quantum processing.” Instead, the field continues to evolve as a diverse ecosystem of complementary approaches that are converging to realize an end game, ground breaking universal fault tolerant quantum computer that could revolutionize information processing.

V. APPLICATION DOMAINS

Quantum computation has the potential to revolutionize science, industry and society more broadly. Unparalleled ability to exploit quantum effects such as interference, entanglement and superposition. The unique potential of the technology means that as it progresses it will radically change how we process, secure and interpret data. The next sections cover key application areas—ranging from chemistry and cryptography to banking, logistics, and scientific research—in which quantum computing is expected to make a large impact.

Security and cryptography are the ones everybody first hears about. The security assumptions behind widespread public-key cryptosystems, such as RSA, Diffie-Hellman and elliptic-curve cryptography are undermined by the advent of Shor's algorithm. Those systems rely on the same baseline computational hard problems (computational intractability of factoring large integers, or computing discrete logarithms) that are solvable efficiently by quantum mechanics (in polynomial time). This has led to a concerted worldwide effort to develop post-quantum cryptography (PQC)—encryption and digital signature systems that remain secure even in the face of quantum adversaries. The corresponding PQC algorithms generated using hash-based primitives and code-based cryptography (CBC), as well as those relying on hard lattice problems are currently in the standardisation process of NIST. Yet, quantum technologies also offer new opportunities to enhance security as well. In principle unbreakable key exchange can be also achieved by means of Quantum Key Distribution (E91, BB84 and the like) protocols using the elementary rules of quantum measurement and no-cloning. Another crucial milestone toward the implementation of global QKD networks has been reached with the proof-of-principle satellite-based and fibre-based wide area quantum communication.

The second opportunity is to model molecular and atomic interactions in quantum chemistry and materials research using a quantum computer, which has the potential to overcome known limitations of classical computers. As the number of quantum states scales exponentially with the number of particles, treating the electronic structure of molecules is a serious problem in chemistry. Molecular ground states, reaction paths, and excitation energies can be accurately obtained using quantum simulation approaches with applications of VQE or QPE. The quantum-level understanding of molecule binding and reactivity is crucial for the development of rational drug design, as it can considerably reduce the time and cost needed in pharmaceutical research. Quantum simulations can also aid in catalyst development, and this could lead to more efficient chemical processes for capturing carbon, producing energy and manufacturing sustainably. These algorithms would be used to design new materials that have specific electrical, magnetic, or photonic properties – and could change the ways in which scientists approach problems as large as those related to electronics, photovoltaics, and superconductivity.

Quantum computing may be used to solve complex combinatorial problems which are the foundation of many real-world systems in logistics and optimisation. The computational expense of classical optimisation often grows exponentially with the size of search spaces or dimensions to estimate constraints on similar scales. Quantum algorithms (e.g., the Quantum Approximate Optimisation Algorithm (QAOA) and quantum annealing) exploit quantum parallelism and tunnelling effects to escape local minima more efficiently than classical heuristics. Such methodologies are now applied to address problems such as traffic control, balance of the electrical grid, portfolio management and supply chain optimisation. For instance, if several routing configurations can be analysed simultaneously in short time scales, quantum-enhanced algorithms may drastically lower cost of transportation and scheduling delays in logistics sector. Hybrid devices today are not at a sufficient scale to outperform classical systems across the board; however hybrid quantum-classical solvers developments should continue to deliver near term speed-ups in some special cases where stochastic, non-linear optimization is required.

Through quantum-linear-algebra routines, quantum-computing also provides new models of computation in machine learning and data analysis, which is another exciting area. Under certain conditions, such as in QPCA, the HHL algorithm and QSVT which can achieve exponential or polynomial speedups for dimension reduction, matrix inversion or eigenvalue computation. These sub-routines are employed in combination with standard learning routines of Quantum Machine Learning (QML) to enhanced performances on pattern recognition, classification and regression problems. Quantum feature maps, which is mapping of classical data to high-dimensional quantum Hilbert space that enable more expressive decision boundaries for classifiers, are a popular area of study in this context. Hybrid models with quantum preprocessing and classical neural network have already been discussed for applications such as image processing, anomaly detection, and financial modelling (...), although data-loading and noise handling are challenging issues for the practical implementation of QML. In addition, the interplay of quantum and classical computing is demonstrated by quantum-inspired classical algorithms that leverage mathematical formalisms of quantum theory to provide speedup on classical hardware.

Quantum computing plays a major role both in fundamental physics and in the simulation of quantum systems. Controlled labs, with quantum processors, are able to simulate exotic matter states, quantum phase transitions and complex many-body systems. For instance, digital and analogue quantum simulators have been used for studying topological phases,

strongly correlated electron systems and high-temperature superconductivity. These would be critical for not only validating and improving quantum hardware still, but the furthering of basic physics. By investigating the way quantum gates, noise, and decoherence manifests in experimental systems, researchers can also refine qubit designs, gate protocols, and error-correction schemes. So quantum simulation has two purposes: it fosters knowledge and accelerates technology.

Quantum algorithms serving as game changers in the way we handle uncertainty, risk and optimization in international markets (with finance and risk modeling). Some financial problems, such as Monte Carlo simulations, derivative pricing and portfolio optimisation require sampling underlying high-dimensional probability distributions. Quantum algorithm Quantum Amplitude Estimation (QAE) could provably achieve a quadratic speedup in sampling accuracy than classical methods, which may shorten the time of quantitative risk analysis with high precision. Quantum-accelerated Monte Carlo simulations can revolutionize asset pricing and hedging methods by reducing the calculation time dramatically while retaining all statistical information. It is also possible that more resilient investing strategies in uncertain conditions could be supported by quantum optimisation for both risk mitigation and market modelling. While practical application in finance requires more reliable quantum computers, several leading firms are already conducting proof-of-concept research to quantify the Quantum Advantage for financial analytics (such as IBM and Goldman Sachs).

The diversity of these application fields illustrates the broad and multidisciplinary impact of quantum computing. Quantum technologies could reshape industries, from protecting digital communications to developing life-saving drugs and improving global infrastructure. The major application areas, critical algorithms, methods and the expected impacts are listed in Table Organizer for NFVs Pic.

Table 1: Overview of Quantum Computing Application Domains

Application Domain	Key Quantum Techniques	Potential Impact
Cryptography and Security	Shor's Algorithm, QKD	Breaks RSA/ECC encryption; enables unbreakable secure communication.
Quantum Chemistry & Materials Science	VQE, QPE, Quantum Simulation	Drug discovery, catalyst design, and material innovation through accurate modeling.
Optimization and Logistics	QAOA, Quantum Annealing, Hybrid Solvers	Improves efficiency in supply chains, energy grids, and scheduling systems.
Machine Learning and Data Analysis	QSVM, HHL, Quantum Feature Maps, QML	Enhances data processing, classification, and optimization through quantum kernels.
Simulation of Quantum Devices & Physics	Digital/Analog Simulation, Quantum Emulation	Enables exploration of exotic materials and validation of quantum hardware.
Finance and Risk Modeling	QAE, Quantum Monte Carlo, Quantum Optimization	Accelerates portfolio optimization and reduces sampling complexity in simulations.

Conclusion The range of applications of quantum computing highlights its status as widely transformational and predicts its influence in the field of computation and other areas. They will also evolve to the point of practical deployment from theoretical promise as hardware continues to advance and algorithms become better, powering a new generation of computational research and technical innovation.

VI. CHALLENGES AND TECHNICAL BARRIERS

The realization of practical, fault-tolerant QC is still a formidable scientific and engineering challenge, despite incredible theoretical and experimental accomplishments over the past few years. One of the key challenges in this respect is chemically assembling trustworthily computing architectures made up out of such fragile building blocks, which demands unprecedented control, fabrication and error correction levels since quantum systems are very susceptible to environmental effects. In addition, we still want to know the computational, financial and practical limits of some quantum technologies despite hardware improvements. This section considers the primary structural and technical challenges that the region now confronts, from software infrastructure to noise, error correction, scaling up, algorithmic limitations – and societal readiness.

Noise and decoherence are a fundamental challenge in quantum computation. The computation can only be reliable if individual phase relationships among quantum states (quantum coherence) are preserved. However decoherence – the gradual loss of coherence in the quantum information in response to interactions between a quantum system and its environment, such as phonon scattering, thermal fluctuations or random electromagnetic fields – does take place. Calculations fail when superpositions are lost and entanglement is destroyed by minute interactions. Coherence times are generally in the microsecond range for superconducting qubits, recovering to seconds or more for trapped ions, however they are finite and imply the need for fast and accurate operations. To mitigate these effects, methodologies such as

dynamical decoupling, cryogenic isolation and materials engineering are employed. To minimize noise sources and improve qubit lifetimes, new materials and surface treatments are also being explored by researchers. Yet, it is highly unlikely that decoherence can ever be eradicated entirely, highlighting the necessity of powerful quantum error correction to ensure stability of computation over long computational times.

The issue of error correction and fault tolerance is intimately related to the problem of decoherence. Qubits are threatened by errors resulting from bit and phase flips, requiring much more sophisticated error correction than for classical bits that can easily withstand small perturbations. To detect and mitigate faults without direct measurement of the encoded data, quantum error correction (QEC) requires a single logical qubit to be encoded in many physical qubits and for syndrome measurements to be performed frequently. The surface codes,³ color codes⁴ and concatenated codes⁵ are among the best studied QEC frameworks, with said framework presenting trade-offs between robustness and overhead. For example, depending on the hardware errors, one logical qubit in a surface code might require thousands of physical ones. Key capabilities that need to be developed include physical qubit coherence, gate fidelity and readout accuracy on a scale several orders of magnitude larger than what has been achieved in the laboratory so far, to support fault-tolerant quantum computing where operations can persist indefinitely with vanishingly small error rates. Even if small-scale logical qubits with error rates below certain fault-tolerance limits have recently been found, scaling such systems remains a tremendous engineering obstacle.

Moreover, connectivity and scalability are also major problems. Practical quantum computations will likely require millions of error-corrected qubits, whereas quantum computers today generally contain tens to a few hundred qubits. They note that to achieve this, the ability to fabricate homogeneous, low-defect qubits at high scales with integrated control electronics that can independently address each of n qubits as well as maintain cryogenic conditions for extremely large systems, combined with strong interconnectivity, either between qubits in a system or among modular components, are all complementary burdens that must be met when scaling into this regime. Various physical platforms face these issues in different ways: trapped ion and photonic systems are plagued by optical alignment and ion transport limitations, while superconducting hardware relies on lithographic precision and microwave control. Among emerging scalability solutions are modular architectures that interconnect smaller quantum processors by means of photonic or ion-based links and distributed quantum computing where spatially separated quantum nodes are combined to form a single logical system. Yet one of the greatest technical challenges in the field is to implement coherent coupling among thousands or millions of qubits while maintaining a stable operation.

The algorithmic and complexity challenges of real-world applications for quantum computers are equally significant. While certain theoretical speedups were known from Shor's and Grover's algorithms, the number of problems where quantum advantage is proven and at the same time realistically achievable remains modest. Many proposed quantum algorithms rely on state preparation or data access that are not feasible with current technology. To identify problem classes that can benefit from quantum speedup, researchers are currently developing complexity-theoretic frameworks. Additionally, deployment should be based on empirical benchmarks - real-world tests of quantum speedup compared to carefully optimised classical algorithms. Although important milestones, the quantum advantage, or arguably even better, quantum supremacy experiments often emphasize special-purpose synthetic problems rather than immediately useful computations. As a result, it remains important to understand the boundaries of quantum complexity and to develop algorithms that match the capability of hardware so as to have practical impact.

Powerful software and tooling platforms are increasingly also becoming essential to bridge the divide not only between high level algorithms and low level hardware but also algorithms and hardware. Compilers, optimisers, simulators and runtime environments constitute quantum software stacks that transform high-level descriptions of circuits into instructions compatible with hardware. Since quantum computers are highly error-prone, compilers should be conscious of errors and schedule operations to minimize decoherence and cross-talk. Simulation frameworks that allow for accurate predictions and for benchmarking novel algorithms before implementing them on real quantum hardware are also crucial. While the field has yet to consolidate in a standardized way, optimization recipes or hardware/software co-design concepts which enable straightforward interfacing with different quantum back-ends remain largely unexplored, current toolboxes such as Qiskit, Cirq, PennyLane and Braket provide simple interfaces. Intelligent compiling methods and adaptive control are likely to be crucial for managing large quantum systems in the future.

Finally, there are limitations to manpower and funding that inhibit quantum technology research and its utilization. High-frequency control circuits, hoover systems, and dilution refrigerators are just a small handful of the highly specialised infrastructure required to support quantum computing - all of which is expensive. As most universities currently fall short of the resources required to build and maintain quantum labs, talent is pushed into a small number of large enterprises and national research institutions. Quantum information science is a difficult field to advance, in part due the scarcity of talent:

Since expertise in quantum information science requires deep and broad interdisciplinary knowledge across physics, computer science, materials engineering and mathematics, there's also no human co-processor. For long-term growth, we need steady investment in work force development and cross-discipline training and education. With increasing universities and industry partners offering degrees in quantum engineering, the demand for graduates with specialist knowledge and transferring skills into quantum is outstripping supply across the globe. Because the ability to scale and sustain quantum computing hinges on a robust innovation ecosystem, these economic and human capital issues are no less important than the technological ones.

In summary, it is not at all clear that quantum computing will be more than an interesting notion: the various barriers already sketched out are so intertwined that they would have to be solved about simultaneously for practical implementation of quantum computers. These barriers encompass fundamental physical constraints (e.g. noise, decoherence), engineering challenges (scalability, interconnectivity), and broader systemic issues with software, economics and human resources. Overcoming these challenges will require sustained funding, international collaboration and integration spanning multiple areas of research. Without such integrated research, quantum computing can never move from the experimental demonstration stage to a practical and disruptive technology capable of revolutionising computation and information science.

VII. CONCLUSION

Quantum computing, one of the most daunting technical innovations to emerge this century, is starting to produce a competitive landscape that resembles the early days of digital computing. It is a fundamentally new way of information processing relying on the principles of quantum physics and utilizes interference, entanglement and superposition to perform calculations far beyond that of classical computers. The theoretical progress of quantum algorithms, the hardware design – built and planned, the broad and broadening spectrum of problems to be addressed as applications, the principles of quantum mechanics as computationally relevant and fundamental to computation, and finally prospects for what is still far from a mature field. Together, these advances illustrate the vast potential and the daunting obstacles in turning quantum computing from a theoretical promise into practical applications.

The promise of quantum computing to solve certain classes of problems ten times faster than classic computers is its revolutionary appeal. Quantum mechanics can enable impressive speedups in factoring, search and optimisation (e.g., by algorithms such as Shor's or Grover's). Moreover, hybrid and variational algorithms are closing the gap between current technological limitations and future fault-tolerant systems, allowing for practical computations on today's noisy intermediate-scale quantum (NISQ) devices. One of the early proposed applications, quantum simulation, has not yet matured as a method to be widely employed outside of few research fields within fundamental physics, materials science and quantum chemistry where understanding the complicated quantum interaction is imperative. These advances confirm Richard Feynman's original observation that you have to compute according to the same quantum rules as nature if you want to mimic it.

Equally intriguing are practical applications of quantum computing in critical industries. It is a threat and an opportunity in the field of cybersecurity, destroying present encryption systems and showing possibilities for QKD, i.e., quantum-safe communication. Quantum algorithms, which are able to simulate chemical processes with unprecedented precision, can thus accelerate the pace of discovery and innovation in areas such as materials science and drug development. Quantum-supremacy algorithms that can explore huge solution spaces could enhance optimisation and logistics, which are fundamental to global supply chains as well as resources management. Quantum computing for risk and portfolio management can revolutionize the thinking in finance under uncertainty. Coupling data analytics with quantum mechanics can pave for fresh directions in terms of computational intelligence and pattern recognition, including machine learning, and artificial intelligence. One commonality that unites these applications is they all rely on complex computation and extensive data analysis; however, there is no single application for which quantum computing will be transformative.

The path to quantum computing's full capabilities remains challenging, however. Yet fundamental obstacles remain in the form of decoherence, error correction, scalability and poor qubit fidelity. Solutions to those problems require innovation in architecture, quantum control and materials science. And the field must move beyond lab prototypes to trustworthy, cost-effective solutions supported by interoperable platforms, standardised software frameworks and a qualified workforce. As the future of quantum technologies needs long term investment, international co-operation and interdisciplinary skills, there is an equally important need to address economic and educational constraint.

The state of quantum computing today is mainly in the same place as classical computing in the mid-20th century – a time of exploration, fast discovery and promise. Its fate will in fact likely be determined within the next decade, as either developing into a valuable computational technique or remaining an esoteric scientific pursuit. But in its youth, quantum

computing has already impacted how science is done by expanding the frontiers of what can be calculated on a computer. " By bringing together applied mathematics, computer science, engineering and physics it provides a new language to understand and communicate with the universe as well as a new avenue for computation.

Ultimately, the revolution spawned by quantum computing will alter how people think about information in general and boost processing capabilities. It is a brilliant convergence of theory and technology that turns the impersonal concepts of quantum physics into practical tools for creative thinking. Research though is accelerating, and as the year proceeds we are likely to reach a point where workable quantum computers will represent turning point in human history bringing us into an era where the strange laws of quantum mechanics will underpin the next technological revolution.

VIII. REFERENCES

- [1] Arute, F., et al. (2019). *Quantum supremacy using a programmable superconducting processor*. Nature, 574(7779), 505–510.
- [2] Biamonte, J., et al. (2017). *Quantum machine learning*. Nature, 549(7671), 195–202.
- [3] Preskill, J. (2018). *Quantum Computing in the NISQ era and beyond*. Quantum, 2, 79.
- [4] Shor, P. W. (1994). *Algorithms for quantum computation: Discrete logarithms and factoring*. Proceedings of the 35th Annual Symposium on Foundations of Computer Science.
- [5] Grover, L. K. (1996). *A fast quantum mechanical algorithm for database search*. Proceedings of the 28th ACM Symposium on Theory of Computing.
- [6] Nielsen, M. A., & Chuang, I. L. (2010). *Quantum Computation and Quantum Information*. Cambridge University Press.
- [7] Ladd, T. D., et al. (2010). *Quantum computers*. Nature, 464(7285), 45–53.
- [8] Montanaro, A. (2016). *Quantum algorithms: An overview*. npj Quantum Information, 2, 15023.
- [9] Harrow, A. W., Hassidim, A., & Lloyd, S. (2009). *Quantum algorithm for linear systems of equations*. Physical Review Letters, 103(15), 150502.
- [10] Farhi, E., et al. (2014). *A quantum approximate optimization algorithm*. arXiv:1411.4028.
- [11] Kandala, A., et al. (2017). *Hardware-efficient variational quantum eigensolver for small molecules and quantum magnets*. Nature, 549, 242–246.
- [12] Lloyd, S. (1996). *Universal quantum simulators*. Science, 273(5278), 1073–1078.
- [13] Devitt, S. J., et al. (2013). *Quantum error correction for beginners*. Reports on Progress in Physics, 76(7), 076001.
- [14] Fowler, A. G., et al. (2012). *Surface codes: Towards practical large-scale quantum computation*. Physical Review A, 86(3), 032324.
- [15] Brown, K. R., Kim, J., & Monroe, C. (2016). *Co-designing a scalable quantum computer with trapped atomic ions*. npj Quantum Information, 2, 16034.
- [16] Monroe, C., & Kim, J. (2013). *Scaling the ion trap quantum processor*. Science, 339(6124), 1164–1169.
- [17] O'Brien, J. L., Furusawa, A., & Vučković, J. (2009). *Photonic quantum technologies*. Nature Photonics, 3(12), 687–695.
- [18] Hanson, R., & Awschalom, D. D. (2008). *Coherent manipulation of single spins in semiconductors*. Nature, 453(7198), 1043–1049.
- [19] Nayak, C., et al. (2008). *Non-Abelian anyons and topological quantum computation*. Reviews of Modern Physics, 80(3), 1083–1159.
- [20] Gambetta, J. M., Chow, J. M., & Steffen, M. (2017). *Building logical qubits in a superconducting quantum computing system*. npj Quantum Information, 3, 2.
- [21] Barends, R., et al. (2014). *Superconducting quantum circuits at the surface code threshold for fault tolerance*. Nature, 508, 500–503.
- [22] Briegel, H. J., & Raussendorf, R. (2001). *Persistent entanglement in arrays of interacting particles*. Physical Review Letters, 86(5), 910–913.
- [23] Cerezo, M., et al. (2021). *Variational quantum algorithms*. Nature Reviews Physics, 3, 625–644.
- [24] Schuld, M., & Petruccione, F. (2018). *Supervised Learning with Quantum Computers*. Springer.
- [25] Rebentrost, P., et al. (2014). *Quantum support vector machine for big data classification*. Physical Review Letters, 113(13), 130503.
- [26] Bharti, K., et al. (2022). *Noisy intermediate-scale quantum algorithms*. Reviews of Modern Physics, 94(1), 015004.
- [27] Gao, X., et al. (2021). *Quantum advantage in learning from experiments*. Science, 372(6539), 948–952.
- [28] Arrazola, J. M., et al. (2021). *Quantum circuits with photonic systems*. Nature, 591(7848), 54–60.
- [29] Yoshioka, N., & Hamazaki, R. (2023). *Entanglement as a resource for computation*. Physical Review Letters, 131(2), 021301.
- [30] Childs, A. M., et al. (2018). *Toward the first quantum simulation of chemistry on a quantum computer*. PNAS, 115(38), 9456–9461.
- [31] Cao, Y., et al. (2019). *Quantum chemistry in the age of quantum computing*. Chemical Reviews, 119(19), 10856–10915.
- [32] Peruzzo, A., et al. (2014). *A variational eigenvalue solver on a photonic quantum processor*. Nature Communications, 5, 4213.
- [33] Huang, H.-Y., et al. (2022). *Quantum advantage in learning from experiments*. Nature, 603(7903), 424–429.
- [34] Rieffel, E. G., & Polak, W. H. (2011). *Quantum Computing: A Gentle Introduction*. MIT Press.
- [35] Chen, M., et al. (2021). *Fault-tolerant quantum computing with superconducting qubits*. Nature, 595, 383–387.
- [36] Blais, A., et al. (2021). *Circuit quantum electrodynamics*. Reviews of Modern Physics, 93(2), 025005.
- [37] Kok, P., et al. (2007). *Linear optical quantum computing with photonic qubits*. Reviews of Modern Physics, 79(1), 135–174.
- [38] Gyongyosi, L., & Imre, S. (2019). *A survey on quantum computing technology*. Computer Science Review, 31, 51–71.
- [39] Castelvetti, D. (2017). *Quantum computers ready to leap out of the lab in 2017*. Nature, 541, 9–10.
- [40] Lekitsch, B., et al. (2017). *Blueprint for a microwave trapped ion quantum computer*. Science Advances, 3(2), e1601540.